

## TUNG-SOL

## HALF WAVE

## HIGH VACUUM RECTIFIER



UNIPOTENTIAL CATHODE

HEATER

35 VOLTS 0.15 AMPERE

AC OR DC

GLASS BULB

5 AA  
BOTTOM VIEW

SMALL 6 PIN OCTAL BASE

THE TUNG-SOL 34Z4GT IS DESIGNED PRIMARILY FOR SERVICE AS A POWER RECTIFIER IN AC-DC RECEIVERS EMPLOYING 150 MA. HEATER TUBES. THE VOLTAGE DROP IS THE SAME AS THAT OF THE 25Z6GT WITH BOTH DIODES CONNECTED IN PARALLEL.

## OPERATING CONDITIONS AND CHARACTERISTICS

AC PLATE VOLTAGE RMS (WITHOUT SERIES RESISTOR)	125 MAX.	VOLTS
AC PLATE VOLTAGE RMS (WITH 100 OHM SERIES RESISTOR)	250 MAX.	VOLTS
PEAK PLATE CURRENT	600 MAX.	MA.
DC OUTPUT CURRENT	100 MAX.	MA.
AVERAGE VOLTAGE DROP AT 200 MA. PLATE CURRENT	16	VOLTS

from RMA release #155, Jan. 6, 1939