


## SYMBOL LEGEND







S401 BAND SWITCH WAFER SECTIONS – (F) INDICATES FRONT OF WAFER – (R) INDICATES REAR OF WAFER, AS SEEN THROUGH FRONT

REV 1 CHANGES
* W100 REPLACED BY POLARIZED PLUG.
* F100 MOVED FROM NEUTRAL TO HOT SIDE OF 117 VAC CIRCUIT.
* S100 MOVED FROM NEUTRAL TO LINE SIDE OF PRIMARY 117 VAC CIRCUIT.
* C316A RENAMED TO C317A. IT IS IN PARALLEL TO C317. AND C316 WAS REMOVED DURING PRODUCTION RUN 9.
* C100A & C100B MOVED DOWNSTREAM OF S100, SO AS TO BE DE-ENERGIZED WHEN RADIO POWERED OFF.
* C100A & C100B UPGRADED TO X1Y1 RATED SAFETY CAPACITORS.
* C102 CHANGED FROM 25 µF TO 22 µF.
* C102 CHANGED FROM 0.5 µF TO 0.47 µF.
* C104A, C104B CHANGED FROM 10 µF TO 15 µF.
* C201, C204, C205, C208 CHANGED FROM 0.006 µF TO 0.0068 µF.
* C306, C311 CHANGED FROM 0.01 µF TO 0.033 µF.
* C402A, C402B CHANGED FROM 10 µF TO 20 µF.
* C403 CHAS CHANGED FROM 250 µF TO 200 µF.
* C412 CHANGED FROM 485 µF TO 470 µF.
* C413 CHANGED FROM 285 µF TO 270 µF.

REV 0
* REDRAWN FROM ORIGINAL PHILCO 46-480 SCHEMATIC.
* MADE ALL NECESSARY EDITS TO REFLECT PRODUCTION RUN 9.

JOSEPH R. BLASDEL
Sheet: /
File: Philco 46-480 Schematic.kicad_sch

**Title: PHILCO 46-480 SCHEMATIC**

| | | |
|---|---|---|
| Size: E | Date: 2025-05-05 | Rev: 1 |
| KiCad E.D.A. 8.0.8 | | Id: 1/1 |